

TM 126

TECHNICAL PRODUCT DATA SHEET

Areas of application & features:

- compact warehouse solution for an easy introduction to digital stock management
- up to 378 storage locations per unit for maximum flexibility in use
- controlled dispensing via electronically locked drawers
- drawers that can be customised to suit different item sizes
- can be expanded in a modular fashion by up to three units of the same cabinet type
- intuitive operation via a control PC, HMI and pre-installed GTMS

The benefits of the TM 126:

- avoid stock-outs through minimum stock levels, stock-out calculation and automatic reordering
- analyses and reports provide transparency and manageability of costs
- lower consumption thanks to controlled, automated removal
- decentralised tool storage, central data maintenance: function to book removals & returns directly from the TM 126

Basic technical data

Weight	220–305 kg (depending on equipment)
Width	831 mm
Depth	760 mm
Height	1,610 mm
Load capacity	100 kg/drawer

Electrical connection data

Operating voltage	110–230 V AC at 50/60 Hz
Power consumption	max. 1.1 kW
Pre-fuse	16 A FI/LS max. 30 mA



Standard software configuration: GTMS Basic

When you purchase the TM 126, you also receive the GTMS Basic logistics module as standard. This supports you in managing your master data, creating evaluations and handling intralogistics processes cleanly:

- manage master data: user data, cost units, partners & suppliers, article data
- book tool movements
- manage inventory
- handle order processes & materials planning
- evaluate logistics data: booking data, inventory overview, individual reports, data export

Drawer usable dimensions

	Front height 60 mm	Front height 120 mm
Drawer or front height	3 x 60 mm	6 x 120 mm
Drawer usable height	43 mm	103 mm
Working width	700 mm	
Usable depth	570 mm	
Usable storage area	3.6 m ²	
Usable volume	0.05 m ³	0.25 m ³

Partitioning material

	Front height 60 mm	Front height 120 mm
Longitudinal partitions	6 pieces	6 pieces
Transverse partitions	35 pieces with 100 mm	35 pieces with 100 mm
Recess set	on request	on request
Anti-slip mat	on request	on request

Configuration of the TM 126

Drawer position	Shelf height	Partitioning material		Usable dimensions
		Longitudinal partitions	Transverse partitions	Width x depth x height
Drawer 1 – 3	60 mm	6 pieces	35 pieces with 100 mm	700 x 570 x 43 mm
Drawer 4 – 9	120 mm	6 pieces	35 pieces with 100 mm	700 x 570 x 103 mm

Warranty/conformity:

For materials in Germany, we offer a 12-month warranty on our equipment from the time of commissioning. Our warranty assumes that the device is put into operation in accordance with our regulations and is operated by trained personnel. Changes to the device made by the customer (e.g. changes to the system settings, installation of additional software or hardware components, including hardware components provided by the customer) will render the warranty null and void. We declare that, based on the design and construction and the version placed on the market, the device mentioned in the offer complies with all relevant provisions of the Low Voltage Directive 2014/35/EU and EMC Directive 2014/30/EU – including the amendments applicable at the time of the declaration.

Please note:

The TM 126 must not be used to control third-party systems. The primary reason for this limitation is that the CE conformity of the TM 126 will be invalidated. It is not possible to upgrade and update existing systems to GTMS-V7 by purchasing a TM 126.

Gühring KG

P.O. Box 100247 • 72423 Albstadt • Germany
Herderstraße 50-54 • 72458 Albstadt • Germany

T +49 74 31 17-0
F +49 74 31 17-21 279

info@guehring.com
www.guehring.com

No liability can be accepted for printing errors or technical changes of any kind. Our Conditions of Sale and Terms of Payment apply. Available on request.